

ตารางใช้เทียบรุ่น COMPRESSOR R-12 & R-134a

TECHNICAL DATA 'AE' REFRIGERATOR COMPRESSOR

Model	Refrigerant	Displacement	Nominal	Capacity	Factory oil	Matching Refrigerator	
	Type					C.C	Watt / Hr.
Single Door For 'AE' Series R-12 & R-134a							
AE1320AK	R-12	3.11	48	164	385 cc.(M.O)	1.9 - 2.5	54 - 71
AE1320YK	R - 134a	3.7	57	194	296 cc.(P.O)	2 - 3	57 - 85
AE1325AK	R-12	3.3	60	205	385 cc.(M.O)	2 - 3	57 - 85
AE1327AK	R-12	3.6	65	222	385 cc.(M.O)	3 - 4.9	85 - 139
AE1327YK	R-134a	3.9	67	229	296cc.(PO)	3 - 4.9	85 - 139
AE1332AK	R-12	4.04	78	266	325cc.(M.O)	4.5 - 6.9	127 - 195
AE1330YK	R-134a	4.08	79	270	290 cc.(P.O)	4.5 - 6.9	127 - 195
AE1336AK	R-12	4.45	88	330	520 cc.(M.O)	6 - 7.9	170 - 224
AE1335YK	R-134a	4.597	93	317	296 cc.(P.O)	6 - 7.9	170 - 224
Two Door For "AE" Series R-12 & R-134a							
AE1343AK	R-12	5.47	110	375	520 cc.(M.O)	6 - 7.4	170 -210
AE1340YK	R-134a	5.11	110	375	296 cc.(P.O)	6 - 7.4	170 - 210
AE1350YK	R-134a	5.99	135	536	296 cc.(P.O)	7.5 - 9	212 - 255
AE1360AK	R-12	7.57	165	563	485 cc.(M.O)	9.5 - 10.9	269 - 309
AE1360YK	R-134a	6.91	158	539	485 cc.(P.O)	9.5 - 10.9	269 - 309
AE1380AK	R-12	8.84	194	662	510 cc.(M.O)	11 - 13	312 - 368
AE1370YK	R-134a	8.115	186	635	485 cc.(P.O)	11 - 13	312 - 368
AE2410AK	R-12	12.05	270	921	600 cc.(M.O)	13 - 15	368 - 425
AE1390YK	R-134a	9.423	260	887	450 cc.(P.O)	13 - 15	368 - 425
AE2390Y	R-134a	9.423	260	887	590 cc.(P.O)	13 - 15	368 - 425
AE2413AK	R-12	14.1	330	1126	385 cc.(M.O)	16 - 19	453 - 538
AE2413Y	R-134a	16.08	330	1126	485 cc.(P.O)	16 - 19	453 - 538
AE2415AK	R-12	16.08	380	1296	385 cc.(M.O)	20 - up	566 - up
AE2415Y	R-134a	16.08	380	1296	485 cc.(P.O)	20 - up	566 - UP

NOTE:

M.O = MINERAL OIL

P.O = POLYOLESTER OIL